

MATERIAL SAFETY DATA SHEET

ORANGE #7151

MANUFACTURER'S NAME: THE SHERWIN-WILLIAMS COMPANY
 Distributed by:

EMERGENCY TELEPHONE NO.
 800-535-5053

RUBACHEM SYSTEMS, INC.

P O BOX 901
 NORTHVALE, NJ 07647

DATE OF PREPARATION
 05-MAR-01

INFORMATION TELEPHONE NO.
 (800) 548-3285

Section I -- PRODUCT IDENTIFICATION

PRODUCT NUMBER	7151	HMIS CODES	
		Health	2*
		Flammability	4
		Reactivity	0

PRODUCT NAME
 KRYLON* Upside Down Fluorescent Marking Paint (Solvent-Based), Orange

PRODUCT CLASS
 Aerosol Coating

Section II HAZARDOUS INGREDIENTS

INGREDIENT CAS No.	% by WT	ACGIH TLV	OSHA PEL	UNITS	V. P.
Propane 74-98-6	14	2500	1000	PPM	760.00
Butane 106-97-8	6	800	800	PPM	760 00
Hexane 110-54-3	9	50	50	PPM	127.00
Isohexane Isomers. 107-83-5	7 STEL	500 1000	500	PPM	250.00
V. M. & P. Naphtha. 64742-89-8	7 STEL	300	300	PPM	12.00
Xylene. 1330-20-7	2 STEL	100 150	100	PPM	5.90
Acetone. 67-64-1	9 STEL	500 750	1000	PPM	180.00
Quartz 14808-60-7	21	0.1	0.1	mg/m3 as Resp. Dust	
Barium Sulfate. 7727-43-7	8		10 10(5)	mg/m3 as Dust ***	

*** Total Dust (Respirable Fraction)

KD-7151

PRODUCT WEIGHT 7.54 lb/gal 903 g/l
SPECIFIC GRAVITY 0.91
BOILING POINT <0 - 325 F <-18 - 162 C
MELTING POINT Not Available
VOLATILE VOLUME 79 %
EVAPORATION RATE Slower than ether
VAPOR DENSITY Heavier than air
SOLUBILITY IN WATER N. A.
VOLATILE ORGANIC COMPOUNDS (VOC Theoretical)
Volatile Weight 47.18 % Less Federally Exempt Solvents
HMIS -- 2* 4 0

Section IV -- FIRE AND EXPLOSION HAZARD DATA

FLASH POINT LEL UEL
Propellant < 0 F 0.9 12.8

EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS

Isolate from heat, electrical equipment, sparks, and open flame. Closed containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible auto-ignition or explosion when exposed to extreme heat.

Section V -- HEALTH HAZARD DATA

ROUTES OF EXPOSURE

Exposure may be by INHALATION and/or SKIN Or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.

ACUTE Health Hazards

EFFECTS OF OVEREXPOSURE

Irritation of eyes, skin and respiratory system. May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists-

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

Continued on page 3

EMERGENCY AND FIRST AID PROCEDURES

- If INHALED: If affected, remove from exposure. Restore breathing. Keep warm and quiet'.
- If on SKIN: Wash affected area thoroughly with soap and water. Remove contaminated clothing and launder before reuse.
- If in EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.
- If SWALLOWED: Do not induce vomiting. Get medical attention immediately.

CHRONIC Health Hazards

Crystalline Silica (Quartz, Cristobalite) is listed by IARC and NTP. Long term exposure to high levels of silica dust, which can occur only when sanding or abrading the dry film, may cause lung damage (silicosis) and possibly cancer.

Prolonged and repeated exposure to Hexane may cause damage to nerve tissue of the arms and legs (peripheral neuropathy), resulting in muscular weakness and loss of sensation. This effect may be increased by the presence of Methyl Ethvl Ketone.

Prolonged overexposure to solvent ingredients in Section II may cause adverse effects to the liver, urinary and reproductive systems.

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Section V**REACTIVITY DATA**

STABILITY -- Stable

CONDITIONS TO AVOID

None known.

INCOMPATIBILITY

None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, carbon Monoxide

HAZARDOUS POLYMERIZATION

will not occur

Section VII -- SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate and remove with inert absorbent.

WASTE DISPOSAL METHOD

waste from this -product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Do not incinerate. Depressurize container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

Section VIII-- PROTECTION INFORMATION

PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. wash hands after using.

This coating may contain materials classified as nuisance particulates (listed 'as Dust' in Section II) which may be present at hazardous levels only during sanding or abrading of the dried film. if no specific dusts are listed in Section II, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m3 (total dust), 3 mg/m3 (respirable fraction), OSHA PEL 15 mg/m3 (total dust), 5 mg/m3 (respirable fraction).

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section II is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section II.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

PROTECTIVE GLOVES

None required for normal application of aerosol products where minimal skin contact is expected. For long or repeated contact, wear chemical resistant gloves-

EYE PROTECTION: Wear safety spectacles with unperforated side shields.

Section IX: PRECAUTIONS

DOL STORAGE CATEGORY: 1A PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively.

During use and until all -vapors are gone: Keep area ventilated Do not smoke Extinguish all flames, pilot lights, and heaters Turn off stoves, electric tools and appliances, and any other sources of ignition.

Consult NFPA Code. Use approved Bonding and Grounding procedures.

Contents under pressure. Do not puncture, incinerate, or expose to temperature above 120F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst. Do not take internally. Keep out of the reach of children.

OTHER PRECAUTIONS: Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

Section X OTHER REGULATORY INFORMATION

SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No.	CHEMICAL/COMPOUND	% by WT	* Element
110-54-3	Hexane	9	
1330-20-7	Xylene.	2	

CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.
